

자동구출 운전장치 EP-ARD

EP-Automatic Rescue Dvice Specification

- 지진, 정전 감지 기능
Sensing function of earthquake and blackout
- 기동시간 8분 이내로 구출가능
Possible to rescue within 8 minutes
- 승강기와의 원격제어 지원
Remote control support for elevator



EP-ARD 사양

Model	EP-ARD-02k	EP-ARD-04k	EP-ARD-06k
Maximum output capacity	2[kVA]	4[kVA]	6[kVA]
Output	3phase 4wire		
Nominal power	3phase 380 [vac]		
Frequency	60 [Hz]		
BATT Voltage/Capacity	48V / 18[Ah]	48V / 30[Ah]	48V / 65[Ah]
BATT Quantity	ES18-12 x4	ES30-12 x4	ESH(L)65-12 x4
BATT SIZE(LxWxH)	181x76x167	192x130x170	325x166x174
BATT Weight	5.9x4EA=23.6[kg]	9.3x4EA=37.2[kg]	20.9x4EA=83.6[kg]
BATT TYPE	Rocket ES Type, Storage battery		
BATT attachment	External		
Applied MOTOR	< 11 [kW]	< 15 [kW]	< 24 [kW]
Rescue operation speed	6 [m/min]		
Rescue operation time	8 [min]		
ARD Control panel SIZE (WxDxH)	370 x 375 x 215 [mm]		
ARD Weight	5 [kg]		
BAT Encloure SIZE (WxDxH)	700 x 350 x 300 [mm]		
Total weight (ARD+BATT)	49 [kg]	62 [kg]	110 [kg]